



CHAIN No	PITCH						Width Between Inner Plates
	P						b1
	mm						min mm
FV 40	63	80	100	125	150	160	18,0
FV 63	63	80	100	125	150	160	22,0
FV 90	80	100	125	150	160	175	25,0
FV 112	100	125	150	160	175	200	30,0
FV 140	100	125	150	160	175	200	35,0
FV 180	125	150	160	175	200	250	45,0
FV 250	125	150	160	175	200	250	55,0
FV 315	159	160	175	200	250		65,0

CHAIN No	Bush Ø	Pin Length	Pin Ø	Plate Depth	Plate Thickness	Ultimate Tensile Strength	Free Dimension
	d2	L1	d1	g	s	Q	L
	mm	mm	mm	mm	mm	kg	mm
FV 40	15,0	36,0	10,0	25,0	3,0	4.200	☆
FV 63	18,0	44,0	12,0	30,0	4,0	6.400	☆
FV 90	20,0	52,0	14,0	35,0	5,0	10.000	☆
FV 112	22,0	62,0	16,0	40,0	6,0	12.000	☆
FV 140	26,0	69,0	18,0	45,0	6,0	14.500	☆
FV 180	30,0	87,0	20,0	50,0	8,0	27.000	☆
FV 250	36,0	100,0	26,0	60,0	8,0	27.000	☆
FV 315	42,0	115,0	30,0	70,0	10,0	37.000	☆

☆ A richiesta.
☆ According to request.